

UNITED STATES PATENT AND TRADEMARK OFFICE  
CERTIFICATE OF CORRECTION

PATENT NO. : 6,802,910 B2  
DATED : October 12, 2004  
INVENTOR(S) : Katsuya Murakami et al.

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 1.

Line 38, "be" should read -- to be --.

Column 7.

Line 32, "20 mm 40 mm" should read -- 20 mm-40 mm --.

Column 13.

Line 36, "assembled In" should read -- assembled. In --.

Column 14.

Line 27, "mains" should read -- main --.

Column 15.

Line 57, "the" should read -- of the --.

Column 16.

Line 47, "never" should read -- member --.

Column 17.

Line 30, "moved" should read -- move --.

Column 19.

Line 53, "0.5 mm 5 mm" should read -- 0.5 mm—5 mm --.

Column 20.

Line 5, "silicon" should read -- silicone --.

Column 21.

Line 66, "maker" should read -- member --.

Column 22.

Line 37, "301" should read -- 301*i* --.

Column 24.

Lines 19 and 23, "relative" should read -- relatively --.

101040763

UNITED STATES PATENT AND TRADEMARK OFFICE  
CERTIFICATE OF CORRECTION

PATENT NO. : 6,802,910 B2  
DATED : October 12, 2004  
INVENTOR(S) : Katsuya Murakami et al.

Page 2 of 2


It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 25.

Line 8, "said" should read -- the --.

Signed and Sealed this

Nineteenth Day of April, 2005



JON W. DUDAS  
*Director of the United States Patent and Trademark Office*